

## FOSSER Garant Diesel 15W-40

1 liter, 4 liters, 5 liters, 20/ 25 liters, 60 liters, 208 liters

### High-performance universal engine oil

#### Properties

**FOSSER Garant Diesel 15W-40** is a mineral high-performance universal engine oil of viscosity class SAE 15W-40. Base oils produced with the latest refinery technology and carefully selected innovative additives guarantee that the product meets the highest requirements. Among its most outstanding properties are the excellent shear stability at high temperatures and exceptional wear protection under all operating conditions. Cleaning additives prevent deposits, keep pistons and valves clean and protect the engine against black sludge. Clean engines and low friction reduce energy loss in the engine and minimise servicing costs.

#### Use instructions

**FOSSER Garant Diesel 15W-40** is a high-performance engine oil for universal use, even under high loads. The performance spectrum covers the requirements of passenger car diesel engines with and without turbocharging. The high demands placed on modern, low-consumption engines to fulfil the stricter emission standards are met with reserve.

**Specifications:** ACEA B4, API CF

**Recommendations\*:** VW 505.00

TYPICAL VALUES	METHOD	UNIT	FOSSER Garant Diesel 15W-40
Density at 15°C	DIN 51 757	kg/m <sup>3</sup>	873
Viscosity at 40°C	DIN 51 562	mm <sup>2</sup> /s	115
Viscosity at 100°C	DIN 51 562	mm <sup>2</sup> /s	15,3
Viscosity index (VI)	DIN ISO 2909	-	140
Viscosity at -20°C	DIN 51 377	mPa.s	5380
Pour point	DIN ISO 3016	°C	-42
COC flash point	DIN ISO 2592	°C	230
Total base number	DIN ISO 3771	mg KOH/g	10,1

The stated values may vary within the usual commercial range.

\* meets the requirements of the OEM manufacturer.