



ENEOS X PRIME 5W-40 SN

FULLY SYNTHETIC PREMIUM MOTOR OIL

Material Code: EMA1004

ENEOS X PRIME is a New Premium Engine Oil developed with reference to the voices of ENEOS service stations nationwide. In order to further improve customer satisfaction, it was developed with a focus on "ride comfort," which is our unique index, in addition to fuel efficiency and acceleration performance. In addition to meeting the performance requirements of the latest engine oil standards (API SN, ACEA C3), the ride comfort has been greatly improved by reduced engine noise and vibration resulted by significantly reduced friction.

❖ SPECIAL FEATURES

1. Outstanding oxidation Stability at High temperatures.

ENEOS X PRIME 5W-40 meets the latest API SN standard for gasoline oils.

2. Excellent Engine Cleanliness and Water Resistance.

ENEOS X PRIME 5W-40 SN excellent engine cleanliness and wear resistance have been proven in official laboratory tests in the United States. This performance has also been confirmed in the fill range of vehicle tests.

3. Little Oil consumption

The consumption of motor oils depends largely on the type of base oil, ENEOS X PRIME 5W-40 SN motor oil is blended from high performance Oils, it has little Oil consumption, so users can look forward to adding less Oil to their engines.

4. Meets Latest API & ACEA Standard

The outstanding performance of ENEOS X PRIME 5W-40 SN is proven by its certification for the SN Specification, the latest Motor Oil standard issued by the American Petroleum Institute and European vehicle with ACEA C3.

❖ PERFORMANCE LEVEL

API SN
ACEA C3

❖ APPLICATIONS.

Motor Oil for Gasoline Engines.
Sports cars with large displacements and high outputs, high-performance passenger cars, racing-specification cars, etc.
(To avoid troubles, please use proper viscosity grade oil for the car).

❖ TYPICAL PROPERTIES.

SAE Viscosity Grade Quality Grade	5W-40 SN
Density (15°C), g/cm ³	0.851
Flash Point (COC), °C	234
Kinematic Viscosity (40°C), mm ² /s	80.0
(100°C), mm ² /s	13.5
Viscosity Index	172
Pour Point, °C	-45
TAN, mg KOH/g	1.5
TBN (HCL), mg KOH/g	6.8
Colour (ASTM)	L5.0

❖ PACK SIZE

4L

Note: The Typical Properties may be changed without notice.



Handling Precautions

▼ Follow these precautions when handling this product.

Composition:	Base Oil, Thickener, Additives
Precautionary pictograms:	Not applicable
Signal word:	Not applicable
Hazard Statement:	Not applicable
Precautionary Statements: Prevention	Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not allow the eyes to become exposed to the product. Do not swallow the product. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.
Response	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If the eyes are exposed to the product: Rinse the eyes with plenty of running water and immediately contact a physician. IF ON SKIN: Wash with plenty of soap and water.
Storage	The product must be stored in a cool, well-ventilated location where it will not be exposed to direct sunlight. Containers that have been opened must be tightly sealed.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations. If there are any doubts about proper methods of handling the product, contact the point of purchase before proceeding with usage.