

FOSSER ATF Multi (Natural, Red)

1 liter, 4 liters, 20 liters, 60 liters, 208 liters

Synthetic automatic transmission fluid

Properties

Extremely high viscosity index
High load capacity, outstanding wear minimisation
Low pour point
No foaming
High thermal stability
Reliable friction coefficient characteristic
Unrivalled viscosity-temperature behaviour
Excellent oxidation stability
No adverse effect on standard sealing materials

Use instructions

Automatic motor vehicle transmissions and torque converters
Hydrostatic transmissions
Power steering systems
Hydraulic systems

Observe manufacturer instructions!

Recommendations*: Aisin Warner JWS 3309, Allison C-4, TES-295, TES-389, BMW/Mini P/N 81 22 9 400 272/275, BMW/Mini P/N 81 22 9 407 858/859, BMW/Mini P/N 83 22 0 024 249/359, BMW/Mini P/N 83 22 0 026 922 (BMW 7045 E), BMW/Mini P/N 83 22 0 402 413, BMW/Mini P/N 83 22 0 403 248/249, BMW/Mini P/N 83 22 7 542 290, BMW/Mini P/N 83 22 9 407 765 (BMW LA 2634), Chrysler/Dodge/Jeep AS68RC ATF, Chrysler/Dodge/Jeep ATF+2/ATF+3/ATF+4, Chrysler/Dodge/Jeep SP-III, DTFR 38B100 (236.3), DTFR 13C110 (236.11), DTFR 13C140 (236.7), DTFR 13C150 (236.8), DTFR 13C170 (236.9), DTFR 13C180 (236.91), MB 236.5, 236.6 236.10, Ford WSS-M2C919-E (Mercon V), Ford/Lincoln/Mercury P/N XT-2-QDX [M], Ford/Lincoln/Mercury P/N XT-2-QSM [Syn], Ford/Lincoln/Mercury P/N XT-5-QM or -DM [V], Ford/Lincoln/Mercury P/N XT-8-QAW [Premium], Ford/Lincoln/Mercury P/N XT-9-QMM5 [FNR5], Ford/Lincoln/Mercury WSS-M2C922-A1, GM Dexron II / II-D / II-E / III-G / III-H, GM/GMC/Opel/Saturn P/N 19 40 700/767, GM/GMC/Opel/Saturn P/N 21005966 (transaxle), GM/GMC/Opel/Saturn P/N 22717466, GM/GMC/Opel/Saturn P/N 88900925/9986195, GM/GMC/Opel/Saturn T-IV, Type A Suffix A, Jaguar JLM 20238 / 20292 / 21044 / K17, Jaguar WSS-M2C922-A1, Land Rover Texaco ETL-7045E, MAN 339 A, Mercon V, Mobil ATF 3309, Porsche P/N 000 043 204 41, Porsche P/N 000 043 205 09, Porsche P/N 999 917 547 00 (A2), PSA Peugeot Citroen P/N Z 000169756, Renault Matic D2, Renk Genuine Oil, Saab 3309 – T-IV, Shell 3403-M115, LA 2634, Texaco ETL 7045E / 8072B, N402, Voith H55.6335.XX, Voith Svc Bltn # 013 / 118, Volvo P/N 1161521, Volvo P/ 1161540 / 1161640, Volvo P/N 1273,41, VW/Audi G 052 025 A2, G 052 055, VW/Audi G 052 162 (A1, A2), VW/Audi G 052 990 (A2), C 055 025 (A2), VW/Audi US 000 162, ZF TE-ML 11A / 11B

TYPICAL VALUES	METHOD	UNIT	FOSSER ATF Multi
Density at 15°C	DIN 51 757	g/cm ³	850
Viscosity at 40°C	DIN 51 562	mm ² /s	38,5
Viscosity at 100°C	DIN 51 562	mm ² /s	7,1
Viscosity index (VI)	DIN ISO 2909	-	150
Pour point	DIN ISO 3016	°C	-45
COC flash point	DIN ISO 2592	°C	224
Colour	-	-	natural / red

The stated values may vary within the usual commercial range.

* meets the requirements of the OEM manufacturer.