

FOSSER Brake Fluid DOT 4

250 ml, 500 ml, 1 l

Brake fluid

Properties

Synthetic fluid.

High dry and wet boiling point, reducing vapour bubble formation.

Excellent protection for all metal parts in the brake system against corrosion.

Good protection against wear and foaming.

Compatible with all seals and hoses installed in the brake system.

Use instructions

FOSSER Brake Fluid DOT 4 is recommended for use in brake and clutch systems in vehicles that require a synthetic DOT 4 brake fluid. **FOSSER Brake Fluid DOT 4** can be mixed with all synthetic brake fluids of the same grade.

Special instructions:

Store brake fluid only in sealed original container.

Brake fluid can cause damage to vehicle paintwork.

Observe manufacturer instructions!

Specifications: FMVSS 116 DOT 4, SAE J 1703, ISO 4925

TYPICAL VALUES	METHOD	UNIT	FOSSER Brake Fluid DOT 4
Density at 20°C	ASTM D4052	g/ml	1.06
Viscosity at -40°C	ASTM D7042	mm ² /s	<1500
Dry boiling point (min.)	SAE J 1704	°C	>230
Wet boiling point (min.)	SAE J 1704	°C	>155

The stated values may vary within the usual commercial range.

* meets the requirements of the OEM manufacturer.