

## FOSSER Garant 15W-40

1 liter, 3 liters, 4 liters, 5 liters, 20 liters, 60 liters, 208 liters

### Universal engine oil

#### Properties

**FOSSER Garant 15W-40** is a universal SAE 15W-40 mineral engine oil offering excellent protection against wear and corrosion.

#### Use instructions

**FOSSER Garant 15W-40** is recommended for use in diesel and petrol engines according to the manufacturer instructions. The SAE 15W-40 classification makes it suitable for year-round use under Central European weather conditions.

#### Specifications: API SF/CD

TYPICAL VALUES	METHOD	UNIT	FOSSER Garant 15W-40
Density at 15°C	DIN 51 757	kg/m <sup>3</sup>	880
Viscosity at 40°C	DIN EN ISO 3104	mm <sup>2</sup> /s	96
Viscosity at 100°C	DIN EN ISO 3104	mm <sup>2</sup> /s	13,3
Viscosity Index (VI)	DIN ISO 2909	–	144
Viscosity at -20°C	ASTM D 5293	mPa.s	5.460
Pour point	DIN ISO 3016	°C	-39
COC flash point	DIN ISO 2592	°C	232
Base Number	DIN ISO 3771	mg KOH/g	6

The stated values may vary within the usual commercial range.

\* meets the requirements of the OEM manufacturer.