

FOSSER Mehrzweckfett 2

400 gr, 5 kg, 15 kg, 25 kg, 50 kg, 180 kg

Multi-purpose lithium grease

Properties

Mixable with most conventional soap base grease products.
Good adhesive properties.
Shear-proof and oxidation-resistant.
Wear reducing.
Water resistant.
Prevents corrosion.

Use instructions

Mehrzweckfett 2 is particularly suitable for the lubrication of all types of anti-friction and plain bearings under normal load as well as joints operated at normal temperatures and conditions. This makes it a universal lubricant for automotive vehicles, construction machines and agricultural machinery. When re-lubricating parts, ensure that the grease is not contaminated with dust or dirt particles.

Observe manufacturer instructions!

Specifications: Mehrzweckfett NLGI 2, DIN 51 5825: K2K-30, ISO/DIS 6743-9: ISO-L-XCCHA 2

TYPICAL VALUES	METHOD	UNIT	Mehrzweckfett 2
NLGI grade	DIN 51 818	–	2
Soap/ thickener	–	–	lithium soap
Colour	visuell	–	light brown
Texture	visuell	–	smooth
Operating temperature range	–	°C	-30 to + 120
Penetration at 25°C	ISO 2137	0,1 mm	280-300
EMCOR test	ISO 51 802	Rating	0-0
Drop point	DIN ISO 2176	°C	>190
Viscosity (base oil) at 40°C	ASTM D 7042	mm ² /s	110

The stated values may vary within the usual commercial range.

* meets the requirements of the OEM manufacturer.