

FOSSER Premium GM 0W-20 (Hybrid Approved)

1 liter, 4 liters, 5 liters, 20 liters, 60 liters, 208 liters

HC-Synthetic High-Performance Low-Friction Engine Oil for Passenger Cars

Properties

FOSSER Premium GM 0W-20 is synthetic high-performance low friction engine oil for petrol passenger cars. Base oils made with the latest synthesis technology and carefully chosen innovative additives are combined to produce a lubricant that exceeds today's requirements. Excellent cold start behaviour ensures optimum lubrication during the cold start phase. The product provides reliable protection under extreme conditions and high temperatures. A special combination of active agents based on the latest technology that are specially chosen to match the synthetic components provides unrivalled protection against wear, deposits and black sludge while keeping the engine clean.

As it significantly reduces the fuel consumption, **FOSSER Premium GM 0W-20** helps protect the environment.

Use instructions

FOSSER Premium GM 0W-20 is specially designed for modern gasoline engines where the manufacturer prescribes such low viscosity levels.

FOSSER Premium GM 0W-20 is not suitable for diesel engines.

Specifications: API SP, ILSAC GF-6A

Recommendations*: GM Dexos 1™ Gen 3, Ford WSS-M2C947 A/B1, Ford WSS-M2C962 A, Chrysler MS-6395, Daihatsu, Hyundai, Honda, KIA, Isuzu, Lexus, Mazda, Nissan, Subaru, Suzuki, Toyota

TYPICAL VALUES	METHOD	UNIT	FOSSER Premium GM 0W-20
Density at 15°C	DIN 51 757	kg/m ³	847
Viscosity at 40°C	DIN 51 562	mm ² /s	43,2
Viscosity at 100°C	DIN 51 562	mm ² /s	8,3
Viscosity at -35°C	ASTM D5293	mPa.s	5810
Viscosity index (VI)	DIN ISO 2909	-	172
Pour point	DIN ISO 3016	°C	-45
COC Flash point	DIN ISO 2592	°C	234
TBN	DIN ISO 3771	mg KOH/g	8,0

The stated values may vary within the usual commercial range.

* meets the requirements of the OEM manufacturer.