1 liter, 4 liters, 5 liters, 20 liters, 60 liters, 208 liters

Synthetic High-Performance Low-Friction Engine Oil for Passenger Cars

Properties

FOSSER Premium Plus 0W-40 is a synthetic high-performance low-friction engine oil meeting the most stringent requirements of modern turbocharged and non-turbocharged petrol and diesel engines in passenger cars. Excellent flow properties guarantee optimum cold start behaviour. Thanks to its unrivalled high-temperature stability, the product provides a reliable lubricant film even under extreme conditions. As it significantly reduces the fuel consumption, **FOSSER Premium Plus 0W-40** helps to protect the environment.

Use instructions

FOSSER Premium Plus 0W-40 is a top product for modern petrol and diesel engines in passenger cars with or without turbocharger.

Specifications: ACEA A3/B4, API SN/CF

Recommendations *: VW-Normen 502.00/505.00, BMW Longlife-01, Porsche A 40, MB 226.5, MB 229.5,

Renault RN 0700/ RN 0710, Ford WSS-M2C937-A

TYPICAL VALUES	METHOD	UNIT	FOSSER Premium Plus 0W-40
Density at 15°C	DIN 51 757	kg/m³	839
Viscosity at 40°C	DIN 51 562	mm2/s	74,2
Viscosity at 100°C	DIN 51 562	mm2/s	13,1
Viscosity index (VI)	DIN ISO 2909	-	180
Viscosity at -35°C	DIN 51 377	mPa.s	6000
COC flash point	DIN ISO 2592	°C	230
Pour point	DIN ISO 3016	°C	-42
TBN	DIN ISO 3771	Мд КОН/д	12

The stated values may vary within the usual commercial range.

^{*} meets the requirements of the OEM manufacturer.