

Synthetic high-performance low-friction engine oil for passenger cars**Properties**

FOSSER Premium RSi 5W-40 is a synthetic high-performance engine oil of SAE class 5W-40. Synthetic components combined with carefully selected innovative additives guarantee that the product meets the latest market requirements.

Thanks to the significantly improved engine oil quality of **FOSSER Premium RSi 5W-40**, it offers further enhanced wear protection and keeps the engine perfectly clean, even at extended oil change intervals. The extremely low cold viscosity of the lubricant and its reliable high-temperature viscosity properties guarantee significant reductions in fuel consumption.

Use instructions

FOSSER Premium RSi 5W-40 is the ideal high-performance low-friction engine oil for demanding engines. It is used in petrol and diesel engines in passenger cars, including models with turbocharger and direct injection. The product is recommended for all operating conditions.

Specifications: ACEA A3/ B4, API SN/ CF

Approvals: MB-Approval 229.5

Recommendations*: MB 226.5, VW Norm 502.00/505.00, BMW Longlife-01, Renault RN0700/0710, Opel GM-LL-B-025, Porsche A40, PSA B71 2296

TYPICAL VALUES	METHOD	UNIT	FOSSER Premium RSi 5W-40
Density at 15°C	DIN 51 757	kg/m ³	853
Viscosity at 100°C	DIN 51 562	mm ² /s	14,2
Viscosity index (VI)	DIN ISO 2909	-	172
Viscosity at -30°C	DIN 51 377	mPa.s	6260
Pour point	DIN ISO 3016	°C	-39
COC flash point	DIN ISO 2592	°C	226
TBN	DIN ISO 3771	mg KOH/g	10,2

The stated values may vary within the usual commercial range.

* meets the requirements of the OEM manufacturer.