
DATASHEET 60 Ah AGM VR680







FIAMM NEPTUNE PROFESSIONAL AGM BATTERY DATA SHEET FOR WWW.AVTOALL.

Terminal (mm) & terminal Layout:





Bottem holddown:



UN 2800 Non Spillable battery

(Totally maintenance free, leak-proof and spill proof)



Physical Specification (mm)

Nominal voltage	: 12 Volt
Nominal capacity (20hrs)	: 60 AGM
Cold Cranking performance	: 680 AMP CCA EN
Dimensions length	: 242 ±2mm
Dimensions width	: 175 ±2mm
Dimensions container height	: 190 \pm 2mm
Dimensions total height	: 190 \pm 2mm
Weight	: 17,8 kg

Features FIAMM NEPTUNE / ECOFORCE batteries:

- CO2 saver
- High Crancking, starting Amperage also for start/stop.
- 3* Longer Cycle life than traditional batteries (extreme charge and discharge acceptance).
- Higher resistance to vibrations than conventional batteries.
- Totally maintenance free, leak-proof and spill proof.
- Latest OE Technology and quality for starting and deepcycle purpose (Professional Quality).
- NEPTUNE / ECOFORCE batteries can be mounted in any position!

Non binding data and specification. The manufacturer can introduce, without notice, any modification considered as necessary. 1/3/2018