FLOODED BATTERY

46B24LS (12V45Ah)





CHARACTERISTICS


| Item | | Specifications |
|--------------------------------|--------|--------------------|
| Nominal Voltage | | 12V |
| Nominal Capacity (20HR) | | 45Ah |
| Reserve Capacity | | 70mir |
| Cold Cranking Amps@0°F (-18°C) | | 410A |
| | Length | 236mm (9.29inches) |
| Dimension | Width | 128mm (5.04inches) |
| | Height | 222mm (8.74inches) |
| Approx Weight | | 11.7kg (25.8lbs) |
| Terminal | | 1 |
| Cell layout | | 0 |
| Hold-Down | | B0 |
| Case | | Black-PP Material |
| Cover | | Black-PP Materia |
| Handle | | TS1 |
| | | |

APPLICATIONS


- Car start
- •EV/HEV
- Engine start

POS NEG

- ·High capacity and high CCA
- Long life
- •Advanced lead-calcium alloy technology, maintenance-free design
- •Patented venting system bring less water loss and prevent acid leakage
- •OE quality certification







Leoch International Technology Ltd.

mww.leoch.com

Leoch Batteries Pte Ltd

www.leoch.sg

Leoch Battery Corporation

www.leochamericas.com

Leoch Europe S.A.



GENERAL FEATURES

^{*}Values are subject to variation of +/- 5% in normal manufacturing processes.