

# ATF DCT

## Monograde High Performance Diesel Engine Oil

### Description

Petrol Ofisi ATF DCT is an automatic transmission fluid developed to meet the needs of wet DCT type transmission, produced with synthetic base oils and high technological additive package.

### Applications

It is used in the following applications:

Audi	VW TL 052 182	Mitsubishi	MZ320065 Dia-Queen SSTF-I
Audi	VW TL 052 529	Nissan	Ford M2C936A
BMW (Getrag)	83 22 2 148 578, 83 22 2 148 579, 83 22 0 440 214, 83 22 2 147 477	Peugeot	Peugeot/Citroën 9734.S2
Citroën	Peugeot/Citroën 9734.S2	Porsche (ZF)	Porsche Oil No. 999.917.080.00
Ford/Getrag	Ford M2C936A	Seat	VW TL 052 182
Mercedes-Benz	MB 236.21(001 989 85 03)	Skoda	VW TL 052 182
		Volkswagen	VW TL 052 182
		Volvo	1161838 1161839

### Benefits

- Maximum wear prevention property
- Extended equipment life
- Longer fluid life
- Gasket and oil seal compatibility

### Typical Specifications\*

Density, 15 °C, kg/liter	ASTM D4052	0,855
Flash Point, COC, °C	ASTM D92	222
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D445	42
Viscosity, 100 °C, mm <sup>2</sup> /s		7,95
Viscosity Index	ASTM D2270	165
Pour Point, °C	ASTM D97	-42

\* Values shown may differ between productions.

