

MAXIMA 10W-40^{plus}

Synthetic Motor Oil with Improved New Formulation

Description

Maxima 10W-40 PLUS is a synthetic engine oil with up to 4 times wear protection by virtue of the improved new formulation. It is produced from synthetic base oils and new generation additive packages.

Applications

Suitable for all gasoline and diesel engines in the passenger cars and light commercial vehicles demanding SAE 10W-40 viscosity grade and ACEA A3/B4 engine oil performance level.

Benefits

- Provides maximum fuel economy.
- Keeps engine clean.
- Extends oil change interval.
- Provides best fuel efficiency and increases engine efficiency.
- Contributes to engine life by reducing friction.
- Quick start up at cold weather condition and fast engine wear protection.
- Ensures oil film thickness and provides protection against heavy driving conditions via stable viscosity.

Performance

API SN/CF, ACEA A3/B4, MB 229.3, VW 501 01/505 00

Typical Specifications*

SAE Viscosity Grade		10W-40
Density, 15 °C, kg/liter	ASTM D4052	0,870
Flash Point, COC, °C	ASTM D92	234
Viscosity, 40 °C, mm ² /s	ASTM D445	86,5
Viscosity, 100 °C, mm ² /s		130
Viscosity Index	ASTM D2270	151
Pour Point, °C	ASTM D97	-33

* Values shown may differ between productions.

