

MAXIMA DIESEL LA 5W-30

Fully Synthetic Motor Oil for Vehicle with Diesel Particulate Filter



Description

Maxima Diesel LA 5W-30 is a low-ash, synthetic motor oil for up-to-date gasoline and diesel engines with particulate filter. It offers high reliability and allows maximum reduction of fuel consumption.

Applications

Can be used in high performance passenger cars which have gasoline and diesel engines with particulate filter.

Benefits

- Thanks to the low-ash additives it contains, it ensures superior engine protection and longer oil change intervals.
- Long durability of particulate filter.
- Helps protect the environment by lowering exhaust emission.
- Avoids wears especially during warm-up phase.
- Keeps the engine clean.
- Extends service life for batteries by providing easy start-up even at low temperatures.

Performance

API SN/CF, ACEA C3, BMW LL-04, GM Dexos2, MB - Approval 229.51, Renault RN 0700/0710

Typical Specifications*

SAE Viscosity Grade		5W-30
Density, 15 °C, kg/liter	ASTM D4052	0,848
Flash Point, COC, °C	ASTM D92	228
Viscosity, 40 °C, mm ² /s	ASTM D445	60,4
Viscosity, 100 °C, mm ² /s		11,20
Viscosity Index	ASTM D2270	181
Pour Point, °C	ASTM D97	-42

* Values shown may differ between productions.