

## MAXIMA HYBRID 0W-20

Fully Synthetic Motor Oil



### Description

Maxima HYBRID 0W-20 is the full-synthetic motor oil with low ash, which is designed for the current exhaust emission regulation for the motors of passenger cars and light commercial vehicles having high technology.

### Applications

Maxima HYBRID 0W-20 is the motor oil, which focuses on the fuel saving, which is produced for vehicles with new-generation hybrid technology and light commercial vehicles and passenger cars having gasoline or diesel motor, and which can rapidly respond to the instant lubrication need of the start-stop technology. It can be used for vehicle motors with particulate filter, which demands motor oil at ACEA C5 level.

### Benefits

- Reduces the frictional losses and ensures the fuel saving thanks to the low viscosity.
- Minimizes the cold start and start-stop abrasions in the traffic and extends the motor life.
- Protects the motor for a long time and extends the frequency of the oil change thanks to the stable structure.
- Keeps the motor clean thanks to the structure preventing the generation of residue.

### Performance

API SN/CF, ACEA C5, VOLVO VCC RBS0-2AE, FIAT 9.55535, DSX / DM1

### Typical Specifications\*

SAE Viscosity Grade		0W-20
Density, 15 °C, kg/liter	ASTM D4052	0,850
Flash Point, COC, °C	ASTM D92	236
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D445	47,19
Viscosity, 100 °C, mm <sup>2</sup> /s		9,08
Viscosity Index	ASTM D2270	178
Pour Point, °C	ASTM D97	-48

\* Values shown may differ between productions.