

## MAXIMUS XT 10W-40

Synthetic Heavy Duty Diesel Engine Oil

### Description

High performance heavy duty diesel engine oil produced with synthetic oils. Provides excellent performance in diesel engines working with low or high level of sulfur-containing fuels.

### Applications

Recommended for all trucks, buses, construction machines, agricultural machines and generators with diesel engine, especially with turbocharged and low emission engines. It is recommended to use Maximus LA 10W/40 for heavy duty diesel engines with DPF and SCR systems.

### Benefits

- Protects engine against wear at high speeds and high temperatures.
- Provides superior protection and fuel economy by excellent lubrication at low temperatures.
- Increases engine efficiency by keeping the engine clean.
- Provides long gasket and seal life.

### Performance

API CI-4, ACEA E7-16, MB 228.3 MAN M3275-1, MTU Type 2, Volvo VDS-3, RENAULT RLD, MACK EO-N, CUMMINS CES 20078, DETROIT DIESEL DDC 93K215, DEUTZ DQC III-10

### Typical Specifications\*

SAE Viscosity Grade		10W-40
Density, 15 °C, kg/liter	ASTM D4052	0,871
Flash Point, COC, °C	ASTM D92	220
Viscosity, 40 °C, mm <sup>2</sup> /s	ASTM D445	100
Viscosity, 100 °C, mm <sup>2</sup> /s		14,70
Viscosity Index	ASTM D2270	153
Pour Point, °C	ASTM D97	-36

\* Values shown may differ between productions.

