

AVISTA pace EVO GER SAE 5W-40

Powerful, easy running car engine oil (petrol, diesel) of the AVISTA pace EVO line with outstanding cleaning and dispersion properties. Particularly developed for the requirements of German types of vehicle.

APPLICATION

- car, petrol, diesel
- hybrid cars
- may be suitable for engines with an additional gas tank (please observe the respective OEM specifications)

CHARACTERISTICS / APPLICATION BENEFITS

- low evaporation loss and low cam wear
- good oxidation stability
- piston cleanliness
- outstanding cleaning and dispersion properties
- prevents oil inspissation

APPROVALS

API	SN
BMW	LL 01
MB-Approval	229.5

SPECIFICATIONS

ACEA	A3/B4
-------------	-------

RECOMMENDATIONS

API	CF
Fiat	9.55535- M2
GM	GM-LL-B-025
MB	226.5
	229.3
Peugeot	PSA B71 2296 (2014)
Porsche	A40
Renault	RN 0700 / 0710
VW	502 00 / 505 00

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		5W-40
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.842 – 0.872
Kin. Viscosity @ 100 °C	DIN 51562-1	mm ² /s	13.8 – 15.2
Viscosity Index	DIN ISO 2909		min. 165
Total Base Number	DIN ISO 3771	mg KOH/g	10.0 – 12.0
Dyn. Viscosity @ -30 °C	DIN 51377	mPa*s	max. 6,600
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	DIN ISO 3016	°C	max. -39

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 7)