

AVISTA pace EVO C3 SAE 5W-30

Fuel-saving car engine oil (petrol, diesel) of the AVISTA pace EVO line for vehicles with modern after-treatment of exhaust gas and longer maintenance intervals for meeting of all requirements of the ACEA specification C3 and the OEM approvals/specifications stated.

APPLICATION

- car, light commercial vehicles, petrol, diesel, with modern after-treatment of exhaust gas
- hybrid cars
- may be suitable for engines with an additional gas tank (please observe the respective OEM specifications)

CHARACTERISTICS / APPLICATION BENEFITS

- reduced SAPS
- aging resistance
- stability of viscosity
- fuel-saving
- low exhaust gas emissions
- low wear
- engine cleanliness
- longer maintenance interval

APPROVALS

API	SN
BMW	LL 04
MB-Freigabe	229.52 229.51
VW	505 00 / 505 01

SPECIFICATIONS

ACEA	C3
General Motors	dexos 2

RECOMMENDATIONS

MB	229.31
Opel	OV0401547-D30 OV0401547-G30

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		5W-30
Density @ 15 °C	DIN EN ISO 12185	g/cm ³	0.830 – 0.870
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	11.1 – < 12.5
Viscosity Index	ASTM D2270		min. 165
Total Base Number	ASTM D2896	mg KOH/g	7.1 – 9.3
Dyn. Viscosity @ -30 °C	ASTM D5293	mPa*s	max. 6,600
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -36

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 6)