



## FOR WWW.AVTOALL.AZ

|   |                                    |  |
|---|------------------------------------|--|
| Type no.  | AGM 605 01                         |  |
| Article no.   | 016605010101                       |  |
| EAN/GTIN no.  | 9005753083202                      |  |
| Application   | Starter battery start-stop         |  |
| <b>Electrical data</b>  |                                    |  |
| Rated voltage   | 12V                                |  |
| Rated capacity  | 105 Ah (K20)                       |  |
| Cold start current  | 950 A (EN)                         |  |
| <b>Dimensions and weights</b>   |                                    |  |
| Box   | H9                                 |  |
| Length max.   | 394mm                              |  |
| Width max.  | 175mm                              |  |
| Box height max.   | 190mm                              |  |
| Total height max.   | 190mm                              |  |
| Battery weight  | Ca. 29,0 kg (+/- 5 %)              |  |
| Electrolyte density   | Approx. 1,32 kg/l                  |  |
| Electrolyte   | Diluted sulphuric acid             |  |
| Items/pallet  | 36                                 |  |
| Pallet ID   | Euro pallet                        |  |
| Items per layer   | 12                                 |  |
|  |                                    |  |
| <b>Features</b>   |                                    |  |
| Base hold-down  | B13                                |  |
| Layout  | 0                                  |  |
| Terminal  | 1                                  |  |
| Separator   | AGM separator                      |  |
| Degassing   | Battery with central degassing     |  |
| Flame arrester  | Integrated                         |  |
| Performance identification  | W5 - C2 - V3 - M3 (E4)             |  |
| <b>Maintenance 1)</b>   |                                    |  |
| Water consumption   | W5                                 |  |
| Refill water  | Absolutely maintenance-free        |  |
| Self-discharge  | Approx. 3 % per month              |  |
| Charging current  | Approx. 1/20 of the rated capacity |  |
| Charging voltage 2)   | max. 14,8 V                        |  |

1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2020-09-30 ; Rights relating to changes and errors retained.  
original