

TECHNICAL DATA SHEET



FOR WWW.AVTOALL.AZ

Type no.	
Article no.	012740170101
Standards	DIN EN 50342-1, 50342-4
Application	Starter battery
Electrical data	
Rated voltage	12V
Rated capacity	210 AGM
Cold start current	1200 A (EN)
Dimensions and weights	
Box	C
Length max.	517mm
Width max.	273mm
Box height max.	212mm
Total height max.	240mm
Battery weight	Ca. 60,0 kg (+/- 5 %)
Electrolyte density	Approx. 1,28 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	18
Pallet ID	Euro pallet
Items per layer	6
Features	
Base hold-down	B00
Layout	3
Terminal	1
Separator	PE bag separator with glass mat
Degassing	Battery with central degassing
Flame arrester	Integrated
Performance identification	W4 - C2 - >V3 - E3
Maintenance ¹⁾	
Water consumption	W4
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 3 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage ²⁾	max. 14,8 V



FOR WWW.AVTOALL.AZ

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2020-09-30 ; Rights relating to changes and errors retained.
original